

HEATING COOKING APPLIANCE

Patent number: JP1023021
Publication date: 1989-01-25
Inventor: KODAMA SATOSHI; AKIYOSHI MITSUO; MITSUMOTO YOSHIO; WATANABE KENJI; TANAKA MASAFUMI; TSUJIMOTO MASAJI
Applicant: MATSUSHITA ELECTRIC IND CO LTD
Classification:
- International: F24C7/02; F24C15/34; F24C7/02; F24C15/00; (IPC1-7): F24C7/02; F24C15/34
- european:
Application number: JP19870180458 19870720
Priority number(s): JP19870180458 19870720

[Report a data error here](#)

Abstract of JP1023021

PURPOSE: To prevent poor insulation of a heater and increase of the temperature of an outer box to a high value, by a method wherein the whole surface of a surfaceform heater is covered with a heat insulating plate located between the upper part of the outer box and a planar heater, and is inclined such that the level of a front part is increased and that of a rear part is decreased, the upper part of the rear part of the planar heater is bent in an adhering manner to bring a heater surface into a pressure contact with the heater.

CONSTITUTION: A heat insulating plate 13 is situated between the upper part of an outer box 2 and an upper heater 3 placed to the upper part of a heating chamber 1 such that the level of a front part, i.e. the door side, is increased and that of a rear part is decreased. Cooling air to cool a magnetron 9 and a control device 12 is guided to the heating chamber 1, and is discharged through an exhaust hole 6 to the outside together with steam and gas generated during cooking. Leaks through a gap occurs in a route, the steam is adhered to the upper part of the outer box 2 to form waterdrops, which is dropped on a heat insulating plate 13, flows down to the rear part of the heating chamber, and drained through a drain hole 14, formed in the bottom of the outer box 2, to the outside. An adhesion bending part 16 is situated to the upper part of the upper heater 3 and at the rear part of the heat insulating plate 13, and is formed in a manner to make pressure contact with the heater. Even when, during cooking, the ceiling wall of the heating chamber 1 and the upper heater 3 are thermally expanded, adhesion of the ceiling wall of the heating chamber 1 to the upper heater 3 is always uniform, and local heating is prevented from occurring.

